


AC/220 VAC CONTROL UNIT



DC/24 VDC CONTROL UNIT


KONTROL ÜNİTELERİ / CONTROL UNIT

ECORING
2 ACTIVE SENSORS
2 PASSIVE SENSORS

ECORING

KABİN ALTI AŞIRI YÜK
SİSTEMLERİ

OVERLOAD SYSTEMS



ACTIVE



2X

PASSIVE



2X

ECORING TEKNİK BİLGİLERİ

- Mekanik kapasite (Kabin+yük): 2000 kg
- Yüksek hassasiyet ve kolay ayarlanabilme
- 4 ayrı yük için ayarlama
- Besleme gerilimi : 220 VAC / 24 DC
- 0-10 V / 4-20 mA Analog Output
- HOLD girişi: Kabin hareketi esnasında ölçüm sabitleme
- Dijital gösterge
- Değişik kabin tipleri için kalibrasyon imkanı.
- Lastik izolasyonlu
- Otomatik sıfırlama

ECORING TECHNICAL INFORMATION

- Mechanical capacity (cabin+load): 2000 kg
- High precision and easy to adjust
- Programming with keys for different weight points.
- Supply voltage : 220 VAC / 24 DC
- 0-10 V / 4-20 mA Analog output
- HOLD input: To stop the measuring during the travel
- Digital display
- Calibration for different cabin - fixings
- Isolation material is included
- Automatic adjust to zero

ECORING
2 ACTIVE SENSORS
2 PASSIVE SENSORS